MIRAI

experience the future

DTL-332M100

32” / 81 cm LCD TV

HDMI

1000 : 1 Contrast

5 Color Mode

ChroMAX circuitry

Audio Surround

DCI Dynamic Color Improvement

LTI Luminance Transient Improvement

MIRAI
experience the future

DTL-332M100
32” / 81 cm LCD TV

Screen Size	708.95 (H) x 398.59 (V)
Aspect Ratio	16 : 9
Pixel Pitch	0.5190 (H) x 0.5190 (V)mm
Panel Resolution	1366 x 768
Brightness	550 cd/m^2
Contrast Ratio (typ.)	1000 : 1
Response Time (typ.)	8 ms
Viewing Angles (typ.)	176^0 (H) / 176^0 (V)
Display Color	16.7M
Tuner System	PAL, SECAM, NTSC Video
Standard TV	B/G, D/K, I, L/L’
Control Panel	Power (On/OFF), Source Select (SCART 1/SCART 2/TV/AV/SV/VGA/HDMI), Menu (OSD) Operation, Channel Up, Channel Down, Volume +, Volume -, IR Receiver
Terminal I/O	Full SCART - SCART 1: CVBS/RGB(IN), TV(OUT) SCART 2: CVBS(IN), AV/TV(OUT) VGA Input, PC Audio In (for VGA), component video (YPbPr) over VGA Input, audio R/L input HDMI, Headphone Output,
Support Timing	Composite Video+S-Video-R/L Input
Speaker	480i / 480p / 576i / 576p / HDTV (720p / 1080i)
User Controls	8W x 2 Contrast, Brightness, Back Light, Saturation, Colour Temp, Red, Green, Blue, White Balance, Picture Mode, DCI, LTI, Aspect Ratio, Auto (picture setup), Clock, Phase, H-Position, V-Position, CH Scan, Program, Manual Scan, Update Scan, Channel Edit,
Picture Mode	Audio (Balance, Bass, Treble, Surround), Language, OSD Background
Sleep Timer Function	Vivid / Game / Movie / Sport / User
Teletext	Off / 30 min. / 60 min. / 90 min. / 120 min.
Power Supply	252 pages
Power Consumption	AC 220-240 V
Safety / EMC	Operation < 160W
Accessories	TUV-GS / CE / RoHS / WEEE
VESA Mounting	Remote Control, Batteries, User Manual, Power Cord
System Dimension / Carton Size	100 x 200 mm
N.W. / G.W.	944(W) x 522(H) x 207(D) mm / 1050(W) x 600(H) x 280(D) mm
	15 Kg / 15.5 Kg

Jupiterstraat 106, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23 - 567 10 56 FAX +31 (0)23 - 567 10 67
info@nl-mirai.com

www.mirai.eu